NANO SERIES

Power protection at home and office

The Nano UPS provides comprehensive protection in a small and economic package. It is more compact and offers greater comprehensive power protection against surges and spikes. This UPS will continue providing stable power to connected equipment and enable to shutdown PC safely during power failure.

Its embedded microprocessor controller guarantees high reliability. It will automatically restart while AC power is recovering. With Simulated sine wave. And cold start function, it s perfect for any home or small office application.

Model	Nano 400	Nano 600	Nano 800
Capacity	400 VA/ 240 W	600 VA/ 360 W	800 VA/ 480 W
Input/Voltage	110/ 120 VAC or 220/ 230/ 240 VAC		
Input/Voltage Range	90~145 VAC or 180~270 VAC		
Input/Frequence	50Hz or 60Hz		
Output/Voltage	120 VAC or 230VAC ± 10%		
Output/Frequence Range	50Hz or 60Hz ± 1Hz		
Output/Transfer Time(Typical)	2~6 ms		
Output/Waveform(Batt. Mode)	Simulated sine wave		
Battery/Battery Type & Number	12 V/ 4.5 Ah x 1	12 V/ 7 Ah x 1	12 V/ 9 Ah x 1
Battery/Backup Time (One PC load@120W)	5 min.	10 min.	15 min.
Battery/Typical Recharge Time	8 hours recover to 90% capacity		
Physical/Dimension, D x W x H (mm)	228 x 82.5 x 207 (@vertical stand)		
Physical/Net Weight (kgs)	2.2	2.7	3.1